

Model BEAM1224(S) Single-ended Reflected Type Beam Smoke Detector




Models Available

BEAM1224	4 wire conventional beam smoke detector with 8" reflector
BEAM1224S	4 wire conventional beam smoke detector with 8" reflector and integral sensitivity test

Accessories

BEAMLRK	Long range accessory kit (3) additional reflectors (Required for applications in excess of 230 ft. [70m])
BEAMMMK	Multi-mount kit (Provides ceiling or wall mount capability with increased angular adjustment for either the beam or the reflector. When installed with the transmitter/receiver unit, BEAMSMK must be used as well)
BEAMSMK	Surface mount kit
RTS451	Remote test station used to initiate the NFPA sensitivity test function
RTS451KEY	Remote test station with key lock
BEAMHK	Heater kit for transmitter/receiver unit (See electrical requirements on back)
BEAMHKR	Heater kit for reflector (See electrical requirements on back)



Product Overview

- 16 to 328 foot protection range
- Single-ended, reflective design
- User friendly alignment procedure
- 6 user selectable sensitivity levels
- Optional integral NFPA 72 sensitivity test feature
- Removable plug-in terminal blocks
- Digital display for easy alignment
- Built-in automatic gain control compensates for signal deterioration from dust build-up
- Remote test station optional
- Paintable cover
- Easiest alignment in the industry

System Sensor Model BEAM1224 is a 4-wire conventional projected beam smoke detector. It is uniquely suited for protecting open areas with high ceilings where other methods of smoke detection are difficult to install and maintain. It is to be used with UL Listed compatible control panels only. Installation of the single-ended reflective design is much easier than the dual-ended projected beam detectors. Alignment is quickly accomplished via an optical sight and a 2-digit signal strength meter incorporated into the product. Listed for operation from -22°F to 131°F, BEAM1224 can be used in open area applications to provide early warning in environments where temperature extremes exceed the capability of other types of smoke detection.

BEAM1224 consists of a transmitter/receiver unit and a reflector. When smoke enters the area between the unit and the reflector it causes a reduction in the signal and, when the smoke level reaches the predetermined threshold, an alarm is activated.

BEAM1224 has four standard sensitivity selections along with two Acclimate settings. When either of the two Acclimate settings are selected the detector will automatically adjust its sensitivity using advanced software algorithms to select the optimum sensitivity for the specific environment.

BEAM1224S is equipped with an integral sensitivity test feature that consists of a test filter attached to a servo motor inside the detector optics. Using the remote test station RTS451, the motor is activated and moves the filter in the pathway of the light beam, thereby testing detector sensitivity. This integral sensitivity test feature allows the user to quickly and easily meet the annual maintenance and test requirements of NFPA 72.



